

## LISTING OF THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claim 60 (previously presented): A method for storing an electric signal representing recorded ambient noise in compressed form, the method comprising:

periodically recording samples of the ambient noise using a sound transducer;  
normalizing the amplitude of a signal output of the transducer or a signal derived therefrom within a first predetermined range D;  
mapping the normalized amplitude values of the sampled ambient noise onto a second predetermined range of values using a non-linear mapping function to obtain an emphasis of selected values ranges within the first or the second predetermined ranges;  
storing the mapped result in an electronic memory in a digital format.

Claim 1 (canceled).

Claim 2 (previously presented): The method of claim 60, wherein said nonlinear function has a slope  $dW/dD$  which decreases with increasing values in the range D to obtain an emphasis of the smallest values of the first range of values.

Claim 3 (previously presented): The method of claim 60, wherein the mapped result is represented by binary numbers having a fixed number of binary digits from 3 to 16 bits.

Claim 4 (previously presented): A method for storing an electric signal representing recorded ambient noise in compressed form, the method comprising:

periodically recording samples of the ambient noise using a sound transducer;  
normalizing the amplitude of a signal output of the transducer or a signal derived therefrom within a first predetermined range D;

mapping the normalized amplitude values of the sampled ambient noise onto a second predetermined range of values using a non-linear mapping function to obtain an emphasis of selected values ranges within the first or the second predetermined ranges;

storing the mapped result in an electronic memory in a digital format;

10 dividing the audio signal into at least two band signals by filtering, with each one of the band signals containing a frequency range of the audio signal, and wherein any content of the other band signals contained in each band signal is present only in an attenuated form.

6  
Claim 5 (previously presented): The method of claim 4, wherein the audio signal is divided into from 3 to 15 band signals.

4  
Claim 6 (previously presented): The method of claim 4, wherein the band signals essentially contain frequency ranges of the same width each, and all frequency ranges are comprised in the range of 500 Hz to 10,000 Hz.

Claim 7 (previously presented): The method of claim 4, wherein the band signals are generated by splitting once or a cascaded multiple of times an input signal which is either the audio signal or an output signal obtained according to the following steps:

5

- first low pass filtering to generate a first output band signal, and
- subtracting the first output band signal from the input signal to generate a second output band signal.

Claim 8 (previously presented): The method of claim 7, wherein the low pass filtering is realized by means of a digital convolution over 10-30 values.

Claim 9 (previously presented): The method of claim 8, wherein for the purpose of the low pass filtering, the convolution is performed using the terms  $a_i * x_{t-i}$ , wherein the coefficients  $a_i$ ,  $0 < i < 18$ , being approximately equal to {0.03, 0.0, -0.05, 0.0, 0.06, 0.0, -0.11, 0.0, 0.32, 0.50, 0.32, 0.0, -0.11, 0.0, 0.06, 0.0, -0.05, 0.0, 0.03}.

Claim 10 (previously presented): The method of claim 7, wherein the input signal is digitized and only every nth value of each division stage is added to the band signal, n being greater than or equal to 2, in order to compensate for the increased data volume resulting from the splitting into band signals.

Claim 11 (previously presented): The method of claim 60, further comprising generating an energy signal which is proportional to an energy content of the ambient noise from the audio signal or from a signal derived from the audio signal.

Claim 12 (previously presented): The method of claim 11, wherein the energy signal is subjected to a second low pass filtering.

Claim 13 (previously presented): The method of claim 12, wherein the second low pass filtering is effected digitally in the form of a convolution over 20 to 70 values.

Claim 14 (previously presented): The method of claim 13, wherein the second low pass filtering is followed by a second data reduction where one energy value among n filtered values is selected, n being at least equal to 2.

Claim 15 (previously presented): The method of claim 11, further comprising performing a subsequent differentiation of the energy signal with respect to time to obtain an energy difference signal.

Claim 16 (previously presented): A method for storing an electric signal representing recorded ambient noise in compressed form, the method comprising:

periodically recording samples of the ambient noise using a sound transducer;

normalizing the amplitude of a signal output of the transducer or a signal derived therefrom within a first predetermined range D;

mapping the normalized amplitude values of the sampled ambient noise onto a second predetermined range of values using a non-linear mapping function to obtain an emphasis of selected values ranges within the first or the second predetermined ranges;

storing the mapped result in an electronic memory in a digital format; wherein the range of normalized values  $D$  is defined by a lower limit  $D_u$ , and an upper limit  $D_o$ , and wherein the normalization is effected by:

obtaining the maximum of the absolute value of the audio signal or the derived signal within the duration of normalizing the audio or derived signal, which is shorter than or equal to the duration of a hearing sample,

multiplying the reciprocal value of said maximum by  $(D_o - D_u + 1)$ , and

multiplying this product by each value of the audio or derived signal within the duration of the normalized signal.

Claim 17 (previously presented): The method of claim 60, wherein essentially all steps of the method are performed by integer or fixed point arithmetic.

Claim 18 (previously presented): Device for carrying out the method of claim 60, comprising a hearing sample unit comprising at least one signal processor for performing at least one processing step of the method.

Claim 19 (previously presented): The device of claim 18, further comprising a non-volatile semiconductor memory connected to the processor for storing the results of the method.

Claim 20 (previously presented): The device of claim 18, further comprising a timer connected to a power supply of the hearing sample unit for switching off the hearing sample unit when no processing activity is required.

Claim 21 (previously presented): The device of claim 19, wherein a power supply of said non-volatile memory and/or the memory itself is connected to a timer in such a manner that the memory

is essentially capable of being operated only during the storage of the results in order to reduce the energy consumption by the memory.

Claim 22 (previously presented): The device of claim 18, wherein the device is an object which is usually carried by persons.

Claims 23-26: (canceled).

Claim 27 (previously presented): A magnetic, optical or magneto-optical data carrier, containing a recorded program which executes the method according to claim 60.

Claim 28 (canceled).

Claim 29 (previously presented): Device comprising at least one program controlled processor unit and a memory for storing a program controlling the processor unit, wherein the memory contains a program which controls at least one of the operations of the method of claim 60.

Claim 30 (previously presented): The method of claim 60, wherein the electroacoustic transducer is a microphone.

Claim 31 (previously presented): The method of claim 3, wherein the mapped result is represented by binary numbers having a fixed number of binary digits from 4 to 8 bits .

Claim 32 (previously presented): The method of claim 3, wherein the mapped result is represented by binary numbers having 4 bits of binary digits.

Claim 33 (previously presented): The method of claim 4, wherein any content of the other band signals contained in each band signal is attenuated to half of their respective original levels.

Claim 34 (previously presented): The method of claim 4, wherein any content of the other band signals is completely attenuated from each band signal so as to not be present at all therein.

Claim 35 (previously presented): The method of claim 5, wherein the audio signal is divided into from 4 to 10 band signals.

Claim 36 (previously presented): The method of claim 5, wherein the audio signal is divided into from 5 to 8 band signals.

Claim 37 (previously presented): The method of claim 5, wherein the audio signal is divided into 6 band signals.

Claim 38 (previously presented): The method of claim 7, wherein all first low pass filterings have a same Q-factor.

Claim 39 (previously presented): The method of claim 8, wherein the low pass filtering is realized by means of a digital convolution over 15 to 25 values.

Claim 40 (previously presented): The method of claim 8, wherein the low pass filtering is realized by means of a digital convolution over 19 values.

Claim 41 (previously presented): The method of claim 10, wherein  $n$  is equal to 2.

Claim 42 (previously presented): The method of claim 11, wherein the energy signal is generated by squaring said audio signal or said signal derived therefrom.

Claim 43 (previously presented): The method of claim 13, wherein the second low pass filtering is effected digitally in the form of a convolution over 40-55 values.

6  
Claim 44 (previously presented): The method of claim 13, wherein the second low pass filtering is effected digitally in the form of a convolution over approximately 48 values.

Claim 45 (previously presented): The method of claim 13, wherein the convolution has coefficients which are essentially equal to each other.

Claim 46 (previously presented): The method of claim 13, wherein the coefficients of the convolution are equal to 1.0.

Claim 47 (previously presented): The method of claim 14, wherein  $n$  is equal to the number of values of the convolutions of the second low pass filtering.

X  
Claim 48 (previously presented): The method of claim 15, wherein the differentiation is performed by computing the difference between two respective values of the energy signal.

Claim 49 (previously presented): The method of claim 16, wherein  $D_o$  is equal to 0.

Claim 50 (previously presented): The method of claim 16, wherein  $D_u - D_o$  is preferably equal to  $2^n - 1$ ,  $n$  being a whole number greater than 4.

Claim 51 (previously presented): The method of claim 50, wherein  $n$  is equal to 7.

Claim 52 (previously presented): The method of claim 16, wherein the duration of normalizing the audio or derived signal is equal to the duration of a hearing sample.

Claim 53 (previously presented): The method of claim 17, wherein essentially all steps of the method are performed by binary arithmetic with a number of digits as provided by a computing unit performing the method.

Claim 54 (previously presented): The method of claim 20, wherein the timer switches off the hearing sample unit in the periods between the processing of two hearing samples, in order to reduce energy consumption.

Claim 55 (previously presented): The method of claim 22, wherein the device is incorporated in the form of a wristwatch.

Claims 56-59 (canceled).